

# Windows NT File System


„Ausgewählte Betriebssysteme“  
Institut Betriebssysteme  
Fakultät Informatik

## Outline

- NTFS
  - File System Formats
  - File System Driver Architecture
  - Advanced Features
  - NTFS Driver
  - On-Disk Structure (MFT, ...)
  - Compression
  - Recovery Support
  - Encryption Support

## Hardware Basics

- Sector:
  - addressable block on storage medium
  - usually 512 bytes (x86 disks)
- Cluster:
  - addressable block of file system format
  - multiple of sector size



## Win2K File System Formats

- CDFS: ISO 9660 (old CD-ROM FS)
- UDF (Universal Disk Format):
  - ISO 13346 compliant (for optical disk/DVD)
  - Replaces CDFS
  - Filenames can be 255 character long
  - Max path length is 1023 character
  - Filenames can be upper and lower case
- FAT12, FAT16, FAT32
  - FAT12 for anything smaller 16MB
  - FAT16 if explicitly specified (format command)
  - FAT32 anything bigger than 4GB
- NTFS

## NTFS

- For volumes larger than 2GB default cluster size of 4KB is used
- Can (theoretically) address up to 16 exabytes using 64-bit cluster indices
- Limited to address using 32-bit indices → up to 128 TB (using 64KB clusters)

## NTFS Cluster Sizes

Volume Size	Default Cluster Size
512 MB or less	512 bytes
513 MB-1024 MB (1 GB)	1 KB
1025 MB-2048 MB (2 GB)	2 KB
Greater than 2048 MB	4 KB

- Default value can be overridden


## Outline

- NTFS
  - File System Formats
  - File System Driver Architecture
  - Advanced Features
  - NTFS Driver
  - On-Disk Structure (MFT, ...)
  - Compression
  - Recovery Support
  - Encryption Support

## FS Driver Architecture

- Local FSDs:
  - Manage volumes directly connected to computer
  - Responsible for registering with I/O manager
  - First sector on volume identifies volume, its format and location of metadata
- Remote FSDs:
  - Allow access to volumes connected to remote computers
  - Consists of two components (client & sever)


## Local FSD



## Local FSD (2)

- Device object is created for volume by FSD representing FS format
- I/O Manager connects FSD's device object to volume's device object
- Use cache manager to cache FS data (including metadata)
- Cooperate with memory manager:
  - Mapped file cannot be truncated or deleted
- Volume can be dismounted (for raw access)
  - First "normal" access remounts volume

## Remote FSD




## Remote FSD (2)

- Win2K uses Common Internet File System (CIFS) protocol (enhanced version of SMB)
- Client side FSD caches data (to synchronize *oplock protocol* is used)
- File and printer sharing built on it

## Oplock Protocol


- „Opportunistic lock“
- Level I oplock granted for exclusive access (cached read and write)
- Level II oplock granted for shared access (cached read)
- Batch lock is Level I for multiple accesses with close operation in between (no additional oplock when reopening file)

## Oplock Example



- If Client 1 only reads → both get Level II oplock

## File System Operation



## Outline

- NTFS
  - File System Formats
  - File System Driver Architecture
  - Advanced Features
  - NTFS Driver
  - On-Disk Structure (MFT, ...)
  - Compression
  - Recovery Support
  - Encryption Support


## Advanced Features

- Multiple data streams
- Unicode-based names
- General indexing facility
- Dynamic bad-cluster remapping
- Hard links and junctions (soft-links)
- Link tracking
- Per-user volume quotas
- De-fragmentation
- Compression and sparse files (see later section)
- Change logging (see later section)
- Encryption (see later section)

## Multiple Data Streams

- A file consists of streams
- One unnamed, default stream
- Stream name added to file name with colon (`stream.txt:longer`)
- Each stream has separate allocation size
- Each stream has separate file lock

## Unicode Filenames



© Mark Russinovich & David Solomon (used with permission of authors) 19

## Hard Links and Junctions

- Hard links can be created with *CreateHardLink* and *In*
  - Different names link to same file on disk
  - One file contains multiple \$FILE\_NAME attributes
- Junctions are soft links, based on reparse points
  - Reparse point has reparse tag, which allows to identify owner, and reparse data
  - Owner can alter pathname and reissue I/O or
  - Owner can remove reparse point, alter file and reissue I/O (archive and restore file automatically)

Ausgewählte Betriebssysteme - NT File System 20

## Link Tracking

- Links (e.g. shell shortcuts or OLE links) are another mechanism to "soft-link" files
- Link points to unique Object ID, which is stored in \$OBJECT\_ID attribute of file
- Target file can be allocated by querying for the Object ID
- Link tracking service implements the „link following“
- Mapping of Object IDs to filenames stored in file „\$Extend:\$O“ (see slide 29/30)

Ausgewählte Betriebssysteme - NT File System 21

## Quotas

- Files are tagged with security ID (SID) of user
- Logical size of files counts against quota (not compressed size)
- Attempted violations and reached warning thresholds are logged in event log (and administrator can be notified)

Ausgewählte Betriebssysteme - NT File System 22

## Defragmentation




- NTFS does not automatically de-fragment disks
- NTFS provides de-fragmentation API
- Can be used to move file data, and obtain cluster information of file
- Win2K includes de-fragmentation tool

Ausgewählte Betriebssysteme - NT File System 23

## Outline

- NTFS
  - File System Formats
  - File System Driver Architecture
  - Advanced Features
  - NTFS Driver
  - On-Disk Structure (MFT, ...)
  - Compression
  - Recovery Support
  - Encryption Support


Ausgewählte Betriebssysteme - NT File System 24




- ### Outline
- NTFS
    - File System Formats
    - File System Driver Architecture
    - Advanced Features
    - NTFS Driver
    - On-Disk Structure (MFT, ...)
    - Compression
    - Recovery Support
    - Encryption Support
- Ausgewählte Betriebssysteme - NT File System 28

- ### NTFS On-Disk Structure
- Volumes: logical partitions (can span multiple partitions)
  - Cluster: multiple of sector (always power of 2, e.g. 1,2,4,8 sectors)
  - NTFS refers to physical locations on disk by logical cluster numbers (LCNs)
  - NTFS refers to the data within a file by virtual cluster numbers (VCNs)
- Ausgewählte Betriebssysteme - NT File System 29

- ### Master File Table
- All data stored on volume is contained in files:
    - MFT, bootstrap data, allocation bitmap
    - Can relocate metadata
  - MFT is array of file records
  - File record has fixed size of 1KB
  - MFT contains one record for each file on volume
  - Metadata files have name starting with \$
  - On boot, volume is mounted by reading MFT and constructing internal data structures
- Ausgewählte Betriebssysteme - NT File System 30




- ### MFT (3)
- \$Mft and \$MftMirr contain information about MFT (which blocks it occupies, ...)
  - \$LogFile contains recovery information
  - NTFS starts searching for a file in Root directory
  - \$Bitmap shows free clusters
  - \$Secure volume wide security descriptor database
  - \$Boot – bootstrap code must be allocated at specific position on volume, but a file table entry is created, so inform can be read like file
  - \$Volume contains volume name, NTFS version, disk-corruption bit
  - \$Extend contains metadata, like quota, object ID file, ...
- Ausgewählte Betriebssysteme - NT File System 32




- ### File Record
- Strictly speaking: consists of attribute streams
  - Each attribute:
    - Is identified by its attribute code
    - Has a value
    - Has an optional name (used to distinguish attributes of same type)
  - E.g.:
    - \$FILE\_NAME attribute stores file name
    - \$DATA attribute stores content of file
- Ausgewählte Betriebssysteme - NT File System 34

- ### File Record (2)
- Small files fit into record
  - Attributes with values stored in record are called resident attribute (standard information is always resident)
  - Attribute header contains information if it is resident
  - For big attributes clusters are allocated (so-called runs) and referenced from record
  - These attributes are called non-resident
- Ausgewählte Betriebssysteme - NT File System 35



## Non-Resident Attributes

- If multiple runs are needed to store an attribute, a mapping table of VCN is needed
- VCN (location in file), LCN (location on disk and size)



© Mark Russinovich & David Solomon (used with permission of authors) 37


## Directory Lookup

- For fast directory lookup an index tree is maintained
- Tree is B+ tree
- Each entry in tree contains information on file name, size, time stamp → directory information can be displayed without touching the file
- Requires this information to be updated in two places
- Each 4KB index buffer can contain 20-30 filenames

Ausgewählte Betriebssysteme - NT File System

38

## Directory Lookup (2)



© Mark Russinovich & David Solomon (used with permission of authors) 39

## Outline


- NTFS
  - File System Formats
  - File System Driver Architecture
  - Advanced Features
  - NTFS Driver
  - On-Disk Structure (MFT, ...)
  - Compression
  - Recovery Support
  - Encryption Support

Ausgewählte Betriebssysteme - NT File System

40

## Compression

- Compress sparse files (with holes), by not allocating runs for the holes (zeros)




© Mark Russinovich & David Solomon (used with permission of authors) 41

## Compression (2)

- Non-Sparse Data compressed by combining 16 consecutive clusters to *compression units*
- Compress unit and if at least one cluster is saved, store compressed data.
- Distinguish compressed from uncompressed by length of run (number of clusters < 16)
- (runs with less than 16 clusters can be compressed too, but mapping becomes complicated and when stored again, stored in consecutive 16 cluster run)

Ausgewählte Betriebssysteme - NT File System

42



- ## Outline
- NTFS
    - File System Formats
    - File System Driver Architecture
    - Advanced Features
    - NTFS Driver
    - On-Disk Structure (MFT, ...)
    - Compression
    - Recovery Support
    - Encryption Support
- Ausgewählte Betriebssysteme - NT File System 44

- ## Recovery Support
- NTFS uses transaction-processing scheme to implement recoverability
  - Recovery Procedures limited to file system data – user data never guaranteed to be fully updated after crash
  - Sub-operation of transactions that alter file system data are logged before being carried through on disk
  - Logging done by Log File Service (LFS)
- Ausgewählte Betriebssysteme - NT File System 45


- ## Log File Service (LFS)
- Log file divided into *restart area*:
    - 2 copies
    - Contains context information, such as location of start of recovery
  - And *logging area*:
    - Treated as infinite (logs are written looping through area)
  - Logical Sequence Numbers (LSN) used to identify records (64bit)
  - Provides services to NTFS to open/close log file, read/write records
- Ausgewählte Betriebssysteme - NT File System 46

- ## Transaction sequence
- Steps to ensure recoverability:
    1. NTFS calls LFS to record modification
    2. NTFS modifies volume
    3. Cache manager prompts LFS to flush Log to disk
    4. Cache manager flushes the volume changes
  - Log file is also cached
- Ausgewählte Betriebssysteme - NT File System 47

- ## Log Record Types
- Update Records
    - Redo information: how to reapply one sub-operation
    - Undo information: how to reverse one sub-operation
    - Contain physical state of data
  - Checkpoint record
    - Written, when data has been updated in file as well
- Ausgewählte Betriebssysteme - NT File System 48



## Log Record Types (2)



© Mark Russinovich & David Solomon (used with permission of authors) 49

## Recovery


- Depends on two tables
  - Transaction table: keeps track of unfinished transactions
  - Dirty page table: contains modified pages, which contain file system structures
- Once every 5 seconds:
  - Transaction table and dirty page table written to log
  - Checkpoint written to log
- On recovery log-file is scanned three times
  - Analysis
  - Redo transactions
  - Undo transactions

Ausgewählte Betriebssysteme - NT File System

50

## Analysis Pass


- Scan forward in log-file from beginning of last checkpoint operation to find update records to restore transaction and dirty page table
- Oldest update record, which's operation hasn't been carried out on disk, is determined (compared with dirty page table)
- If last checkpoint is older, Redo starts there



© Mark Russinovich & David Solomon (used with permission of authors) 51

## Redo Pass


- Looks for „page update“ records
  - Which contain volume modification written before crash
  - But have not been flushed to disk
  - These updates are redone
  - After pass completed cache updates finished



© Mark Russinovich & David Solomon (used with permission of authors) 52

## Undo Pass

- Roll back any transactions that weren't committed
- Undo operations are logged (in case of another power down)
- After Undo Pass is complete an „empty“ LFS restart area is written



© Mark Russinovich & David Solomon (used with permission of authors) 53

## Outline

- NTFS
  - File System Formats
  - File System Driver Architecture
  - Advanced Features
  - NTFS Driver
  - On-Disk Structure (MFT, ...)
  - Compression
  - Recovery Support
  - Encryption Support

Ausgewählte Betriebssysteme - NT File System

54

## Encryption

- User is assigned a private/public key pair (when he/she first encrypts a file)
- When file is encrypted:
  - content is encrypted using random number called file encryption key (FEK) and DESX (stronger version of DES)
  - FEK is encrypted using public key of user and RSA and attached to file
  - For each user FEK is encrypted respectively

Ausgewählte Betriebssysteme -  
NT File System

55

## Encryption (2)

- Private Key is stored in Registry (on disk “in a safe place”) or smart card
- EFK is also encrypted for each Recovery Agent if recovery policy is defined
- Usage of private key:
  - CryptGetUserKey to tell crypto provider to subsequently use this user's key
  - CryptDecrypt is called to decrypt EFK

Ausgewählte Betriebssysteme -  
NT File System

56

