Real-Time Systems

Time-Driven and Partitioned Systems

Hermann Härtig

TECHNISCHE UNIVERSITÄT DRESDEN

WS 2013/14

Time-Driven vs. Event-Driven Scheduling

Time driven

- at design time, a feasible schedule is computed
- the schedule is stored in a table
- at *certain points* in time, the scheduler dispatches tasks

Event driven

- at design time, the feasibility of a set of tasks is determined depending on the scheduling algorithm
- at certain events, the scheduler computes a schedule and dispatches tasks

Outline

- time-driven in general
  (mostly following Jane Liu, Real-Time Systems)
  - cyclic schedules
  - tick-driven cyclic schedules
  - critical sections and precedence
- time and space partitioned systems
- time-driven communication (later)

Time-Driven Scheduling

Properties:

- decisions, which job to execute next at specific time instants
- these are chosen a priori (before system begins execution)
- schedule is computed off-line

Typically restrictive assumptions: deterministic systems

- fixed number of tasks in systems
- with a priori fairly well known parameters
  (fixed inter-release times)
- tasks must be ready at their release times
- usually used for safety-critical, hard real-time systems

Partitioned Systems

Usage scenario:

- separation of subsystems required for safety and/or security
- Subsystems are potentially very complex
- space partitioning:
  resources are allocated to one partition only
- time partitioning:
  timeline is partitioned into slots
  each slot belongs to one partition exclusively

Derive a Time-Driven Schedule

- sufficient to find schedule for hyperperiod which is called a cyclic schedule

- example: Tasks: (P_i, e_i):
  (4,1) (5,1.8) (20,1) (20,2)
- hyperperiod: 20
- arbitrary possible schedule for one Hyperperiod:



Unused parts can be used for aperiodic jobs

Executing a Cyclic Schedule

store all scheduling points (t_i,$T(t_i)$) in table

```
Do
   set timer to next decision point
   run current job in table
   wait for timer
Done
```

cyclic schedule

- note:
  scheduling actions at instants in time (not events!)
- contrast:
  priority driven systems scheduling decisions occur at events

Tick-Driven Systems (Synchronous Systems)

- scheduling actions only at periodic instants of time
- time line divided into *frames*
- structured variant of cyclic schedules
- no preemption within frames (in the normal case)
- scheduling decisions and check for violations at frame borders
- question: What frame size?



Frame Size f

1. at least one period should be multiple of f
   ensures an integer number of frames per hyperperiod
2. $f \geq \max(e_i)$ (avoids preemption)
3. one full frame (two boundaries)
   between release time t′ and deadline D
   for each job in all periods
   to enable the scheduler checks before deadline



Frame Size f

1. at least one period should be multiple of f
   ensures an integer number of frames per hyperperiod
2. $f \geq \max(e_i)$ (avoids preemption)
3. one full frame(two boundaries)
   between release time t' and deadline D
   for each job in all periods
   to enable the scheduler checks before deadline
   more critical case: $t' > t$: $t + 2f \leq t' + D$



Examples

(4,1) (5,1.8) (20,1) (20,2)



(4,1) (5,2) (20,5)



Slices

decompose jobs in slices: cut messages into segments

- subroutines

example (4,1) (5,2) (20,5):

- cut (20,5) in (20,1) (20,3) (20,1)
- frame size: 4



Problems:

- If T1 in job 2 does not fully use its wcet, T2 runs early
- If T2 (job 3, in 13,15) overruns, scheduler detects at 16

Alternative

better:

- (4,1) (5,2) (20,5)
- cut (20,5) in (20,1) (20,1) (20,2) (20,1)
- frame: 2



A Cyclic Executive

current time t:= 0; current frame k := 0;

at every f time units DO

    get jobs, slices from cyclic schedule

    t:=t+f; k:= t mod hyperperiod;

    react if last jobs/slices have not completed properly

    execute jobs

    take care about aperiodic jobs

DONE

Accommodating Aperiodic Jobs

- Use time not allocated to slices
- objective: improve response time of aperiodic jobs
- slack stealing: execute aperiodic jobs before periodic

Accommodating Sporadic and Aperiodic Jobs

Assumptions:

- known deadline, wcet: S(D,e)
- jobs preemptable

Example:

- remove defective part from conveyer belt, if possible
- otherwise stop the belt

At execution time:

- acceptance test: sum(slack times in all frames before d) $\geq$ e
- generate “slices” that fit in frames
- static: put slices in frames
- dynamic: queue according to EDF (after positive acceptance test)

Practicalities

- frame overruns ...
- incomplete test ...
- transient faults ...

What to do:

- terminate overrunning job
  (may be ok for robust controllers)
- suspend overrunning job/slice and resume it in next frame where it has allocation
- continue overrunning job into next frame

Mode Changes

- Task system static per *operational mode*
- Examples: aircraft control: taxi, start, fly, land, …
  mobile phone: standby, speak, video, …
- Pre-computation of all involved schedules.
- Reconfiguration when mode changes
- Cyclic schedule must be exchanged
- Code and data of new tasks must be brought in
- Use old schedule during reconfiguration, then switch
- Hard/Soft mode changes

Critical Sections

Task 0

```
Do {
   Work
   lock(l)
      Critical section
   unlock(l)
} forever
```

Task 1

```
Do {
   Work
   lock(l)
      Critical section
   unlock(l)
} forever
```

Critical Sections(2)

T_0: (12,1) (12,1) (12,1)

T_1: (4,1) (4,1) (4,1)

Red: critical section



- Split task, schedule critical section as separate slice
- no explicit lock/unlock operations needed
- Complicated in event driven systems (priority inversion)

Additional Topics

- conceptually simple:
  - precedence constraints
  - no concurrency control mechanisms
    e.g. mutexes (no priority inversion problem)
  - known cache interference (context switching)
  - several processors (if global time available)
    not so simple, but feasible
- replica determinism
- reintegration of nodes after faults
- deriving a schedule in the general case is NP-Hard

Space Partitioned Systems

Space partitioning: allocate each resource to 1 partition

Examples

- disk partitioning
- address spaces (for example Unix processes)
- main memory
- IO devices
- caches
- SMP partitioning

Time Partitioned Systems

Time Partitioning

- divide time into slots
- allocate slot to 1 partition

Examples

- CPU
- busses

Implementation of Time Partitioning

… is hard, because:

- Interaction of resources
  for example bus DMA and CPU-speed
- Multi-Processor
  all CPUs or partition CPUs?
  Synchronizing all participating CPUs
  Gang scheduling
- External events

Motivation for Partitioned Systems

- No interference between subsystems
  - prevents misbehaving subsystems to damage other
  - no timing anomalies
- Separate, systematic test of subsystems, deterministic behavior
- Prevents some timing covert channels

Time Driven Communication

- divide network-time into slots
- allocate slots to communication partners
- if sparse time is used, each message can be identified by its (sparse) time stamp
- detecting a missing message becomes simple
- example: TT-Ethernet

Forward pointers

Later in this course

- time-driven communication → TT-Ethernet
- a HLL-language for tick-driven systems → Esterel
- cache partitioning
- partitioning operating systems

Summary

- Static …, except mode changes
- conceptually simple
- easy to test, validate, certify.

- fixed inter-release times